

AQUAHEAT CAPE  
5 SENNA RD, KILLARNEY GARDENS,  
MILNERTON, 7441  
TEL: 0861 50 35 50  
EMAIL: INFO@AQUAHEAT.COM



AQUAHEAT GAUTENG  
UNIT 7, 126 ROAN CR, CORPORATE PARK NORTH,  
MIDRAND, 1685  
FAX: 0866 31 30 19  
WEBSITE: WWW.AQUAHEAT.COM

**TECHNICAL SPECIFICATIONS TF PREMIER SERIES – STAINLESS STEEL COVER**

MODEL	TF PREMIER	TF080/3	TF130/3	TF200/3
HEATING CAPACITY	kW	35	55	91
	BTU/h	120000	187000	306000
HEATING POWER INPUT	kW	7.1	11.6	17.5
RUNNING CURRENT	A	12.7	20.7	31.2
POWER SUPPLY	V/Ph/Hz	380/3/50	380/3/50	380/3/50
COMPRESSOR QUANTITY	No	2	2	3
COMPRESSOR	Type	Scroll	Scroll	Scroll
HEAT EXCHANGER	Type	Titanium In PVC	Titanium In PVC	Titanium In PVC
FAN QUANTITY	Nr	2	2	3
FAN POWER INPUT	W	200 X 2	200 X 2	200 X 2
FAN ROTATE SPEED	RPM	830	850	850
FAN DIRECTION	Vertical / horizontal	Vertical	Vertical	Vertical
NOISE	dB(A)	61	61	62
WATER CONNECTION	mm	50	63	63
WATER FLOW VOLUME	m3/h	12	19.5	17m3 Min / 29m3 Max
WATER PRESSURE DROP	kPa	15	15	16
UNIT DIMENSIONS	Length	1430	1430	2170
	Width	740	740	764
	Height	990	990	1300
SHIPPING DIMENSIONS	Length	1500	1500	2230
	Width	820	820	820
	Height	1130	1130	1547
NET WEIGHT	Kg	239	284	510
SHIPPING WEIGHT	Kg	206	253	433
CIRCUIT BREAKER	Slow curve	15 Amp TP	25 Amp TP	35 Amp TP
	Normal	20 Amp TP	30 Amp TP	40 Amp TP